Seat Belt for Forklift

Seat Belts for Forklift - Described in the Regulation guidelines are the application of operative restraints and seatbelts on lift trucks. It states that the accountability falls on the employers' to be able to ensure that every machine, piece of equipment and tool is utilized properly utilized in accordance to the directions of the maker.

With regards to their inspection, fabrication, use, design and maintenance Rough Terrain forklifts have to satisfy the regulations of ANSI Standard ASME B56.6-1992.

Side boom tractors and mobile equipment together with a Rollover Protective Structure, or ROPS for short, have to include seat belts that satisfy the requirements of the Society of Automotive Engineers, or SAE, Standard J386 JUN93, Operator Restraint System for Off-Road Work Machines. If any mobile machine has seat belts required by law, the driver and subsequent passengers must ensure they utilize the belts every time the motor vehicle is in motion or engaged in operation as this could cause the equipment to become unbalanced and hence, not safe.

When a seat belt or other driver restraint is needed on a lift truck.

While working a lift truck, the seat belt requirements will depend on some factors. Contributing factors to this determination might include whether the the lift truck is outfitted with a Rollover Protective Structure, the type of forklift itself and the year the lift truck was actually manufactured. The manufacturer's directions and the requirements of the applicable standard are referenced in the Regulation.

In the case of powered industrial trucks, ANSI Standard ASME B56.1-1993 refers to an operator restraint device, system, or enclosure. A driver restraint device, system, or enclosure is designed in order to aid the driver in lessening the risk of entrapment of the head and/or torso between the truck and the ground in the event of a tip over. The system or restraint device can include a seat belt, even if a seat belt is not necessarily a part of such machine or system.